



CHART:

P/N	X(FT)	L(FT)	TOLERANCE(MM)
C6-CRBK001	1	1	+15/-0
C6-CRBK002	2	2	+50/-0
C6-CRBK003	3	3	+50/-0
C6-CRBK005	5	5	+75/-0
C6-CRBK007	7	7	+75/-0
C6-CRBK010	10	10	+75/-0
C6-CRBK017	17	17	+150/-0

P1	PAIRS	P2	WIRE COLOR
1	—○—	3	WHITE/ORANGE
2	—○—	6	ORANGE
3	—○—	1	WHITE/GREEN
6	—○—	2	GREEN
5	—○—	8	WHITE/BLUE
4	—○—	7	BLUE
7	—○—	4	WHITE/BROWN
8	—○—	5	BROWN

NOTE:

- CAT.6 UTP 24AWG*4P(7/0.205,BARE COPPER INSULATION:PE)
+CORSS JACKET: BLACK PVC,OD=6.0±0.2MM
- CONN.:P1 & P2: 8P8C PLUG,LONG BODY,SINGLE LAY,GOLD PLATED
50u".
- ASS'Y BOOT:Ø6.2mm (P/N: 060-BOOT-SR3-XX)
- CABLE ASS'Y MUST PASS CONTINUITY TEST.

NET MECHANISM Corp			
www.cabling-ol.net			
SCALE	NONE		REV
UNIT	MM		A
SHEET	1/1	DWG NO.	
DATE	07/10/08		
TITLE	8P8C PLUG/8P8C PLUG		
PART NO.	C6-CRBKXXX		