



CHART:

P/N	X(FT)	L(FT)	TOLERANCE(MM)
C6-CRBK001	1	1	+15/-0
C6-CRBK002	2	2	+50/-0
C6-CRBK003	3	3	+50/-0
C6-CRBK005	5	5	+75/-0
C6-CRBK007	7	7	+75/-0
C6-CRBK010	10	10	+75/-0
C6-CRBK017	17	17	+150/-0

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	○—○	3	WHITE/ORANGE
2	○—○	6	ORANGE
3	○—○	1	WHITE/GREEN
6	○—○	2	GREEN
5	○—○	8	WHITE/BLUE
4	○—○	7	BLUE
7	○—○	4	WHITE/BROWN
8	○—○	5	BROWN

NOTE:

- 1.CABLE:CAT.6 UTP 24AWG*4P(7/0.205,BARE COPPER INSULATION:PE)
+CORSS JACKET: BLACK PVC,OD:6.2±0.2MM
- 2.CONN.:P1 & P2: 8P8C PLUG, LONG BODY, SINGLE LAY, GOLD PLATED
50u".
- 3.ALL BOOT:MOLDING 60P BLACK PVC.
- 4.CABLE ASS'Y MUST PASS CONTINUITY TEST.
- 5.MOLD NO:BOOT-03

MERCHANDISE MOQ	EACH 1PCS
LEAD TIME	12 DAY
CABLE MOQ	
CONNECTOR MOQ	

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	05/07/10			

TITLE
8P8C PLUG/8P8C PLUG

B	CHANGE MOLD TYPE FOR ASS'Y BOOT	05/07/10
A	INITIAL RELEASE	07/10/08
REV	DESCRIPTION OF CHANGE	DATE

PART NO.
C6-CRBKXXX