



P/N	X(M)	L(MM)	TOLERANCE(MM)
C6-F14-BL005	0.5	500	+50/-0
C6-F14-BL010	1	1000	+75/-0
C6-F14-BL020	2	2000	+75/-0
C6-F14-BL030	3	3000	+75/-0
C6-F14-BL050	5	5000	+150/-0
C6-F14-BL075	7.5	7500	+150/-0
C6-F14-BL100	10	10000	+150/-0
C6-F14-BL150	15	15000	+300/-0

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	1	WHITE
2	—○—	2	ORANGE
3	—○—	3	WHITE
6	—○—	6	GREEN
5	—○—	5	WHITE
4	—○—	4	BLUE
7	—○—	7	WHITE
8	—○—	8	BROWN

NOTE:

- 1.CABLE:NO-UL UTP CAT.6 FLAT CABLE.4P\*32AWG(7/0.08,250D).  
INSULATION:HD-PE.OD:(0.5±0.05mm)+OUTER JACKET:PVC,  
OD:(6.0±0.2)\*(1.4±0.15)mm.
- 2.CONN.:P1,P2 8P8C MODULAR,SHORT BODY,  
SINGLE LAY,GOLD PLATED 50u",TWO PART.
- 3.ALL HOOD:MOLDING 60P PVC.
- 4.CABLE ASS'Y MUST PASS CONTINUITY TEST.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	05/16/07			
TITLE 8P8C PLUG/8P8C PLUG				
PART NO. C6-F14-YYXXX				