



C6-SGYXXX
 └───┬─── LENGTH UNIT M
 └───┴─── COLOR

CHART:

P/N	X(FT)	L(MM)	TOLERANCE(MM)
C6-SGY075	75	22500	+300/-0
C6-SGY100	100	30000	+300/-0
C6-SGY200	200	60000	+500/-0
C6-SGY300	300	90000	+500/-0

NOTE:

- CAT.6 UTP 24AWG*4P(1/0.58 SOLID,BARE COPPER INSULATION:HD-PE)
 +CORSS JACKET:GRAY PVC,OD=6.5±0.15MM
- CONN.:P1 & P2: 8P8C PLUG,LONG BODY,SINGLE LAY,W/THREE PARTS,
 GOLD PLATED 50u".
- ASS'Y BOOT:Ø6.2mm,GRAY.
- CABLE ASS'Y MUST PASS CONTINUITY TEST.

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	○	1	WHITE/ORANGE
2	○	2	ORANGE
3	○	3	WHITE/GREEN
6	○	6	GREEN
5	○	5	WHITE/BLUE
4	○	4	BLUE
7	○	7	WHITE/BROWN
8	○	8	BROWN

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM		DWG NO.	
SHEET	1/1			
DATE	12/19/07			
TITLE CAT.6 UTP SOLID 8P8C/8P8C PLUG				
PART NO.		C6-SGYXXX		