



L(MM)	TOLERANCE(MM)
100~499	+15/-0
500~999	+50/-0
1000~4999	+75/-0
5000~14999	+150/-0
15000~49999	+300/-0

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	1	WHITE/ORANGE
2	—○—	2	ORANGE
3	—○—	3	WHITE/GREEN
6	—○—	6	GREEN
5	—○—	5	WHITE/BLUE
4	—○—	4	BLUE
7	—○—	7	WHITE/BROWN
8	—○—	8	BROWN

C6-YYXXX
 LENGTH UNIT FT
 COLOR:BL,GY.

NOTE:

- CAT.6 UTP 24AWG*4P(7/0.205,BARE COPPER INSULATION:PE)
+CORSS JACKET:PVC,OD=6.0±0.2MM
- CONN.:P1 & P2: 8P8C PLUG, LONG BODY, SINGLE LAY, GOLD PLATED 50u"
- ASS'Y BOOT:ø6.2mm
- CABLE ASS'Y MUST PASS CONTINUITY TEST.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE	⊕	REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	03/16/06	TITLE		
		8P8C PLUG/8P8C PLUG		
PART NO.		C6-YYXXX		