



P1

P2

L(MM)	TOLERANCE(MM)
100~499	+25/-0
500~999	+50/-0
1000~4999	+75/-0
5000~14999	+150/-0
15000~49999	+300/-0

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	1	WHITE/ORANGE
2	—○—	2	ORANGE
3	—○—	3	WHITE/GREEN
6	—○—	6	GREEN
5	—○—	5	WHITE/BLUE
4	—○—	4	BLUE
7	—○—	7	WHITE/BROWN
8	—○—	8	BROWN

C6-YYXXX

LENGTH UNIT FT  
COLOR:BL,GY.

NOTE:

- 1.CABLE:CAT.6 UTP 24AWG\*4P(7/0.205,BARE COPPER INSULATION:PE)  
+CORSS JACKET PVC,OD:6.2±0.2MM
- 2.CONN.:P1 & P2: 8P8C PLUG,LONG BODY,SINGLE LAY,GOLD PLATED  
50u".
- 3.ALL BOOT:MOLDING 60P PVC.
- 4.CABLE ASS'Y MUST PASS CONTINUITY TEST.
- 5.MOLD NO:BOOT-03

C	CHANGING DIMENSION TOLERANCE	11/18/13
B	CHANGE MOLD TYPE FOR ASS'Y BOOT	05/07/10
A	INITIAL RELEASE	03/16/06
REV	DESCRIPTION OF CHANGE	DATE

MERCHANDISE MOQ	EACH 1PCS		
LEAD TIME	12 DAY		
CABLE MOQ			
CONNECTOR MOQ			
NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE		REV C
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	11/18/13		
TITLE	8P8C PLUG/8P8C PLUG		
PART NO.	C6-YYXXX		