



PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	1	WHITE/ORANGE
2	—○—	2	ORANGE
3	—○—	3	WHITE/GREEN
6	—○—	6	GREEN
5	—○—	5	WHITE/BLUE
4	—○—	4	BLUE
7	—○—	7	WHITE/BROWN
8	—○—	8	BROWN

L(MM)	TOLERANCE(MM)
100~499	+15/-0
500~999	+50/-0
1000~4999	+75/-0
5000~14999	+150/-0
15000~49999	+300/-0

C6-YYXXX  
 LENGTH UNIT FT  
 COLOR:BL,GY.

NOTE:

- 1.CABLE:CAT.6 UTP 24AWG\*4P(7/0.205,BARE COPPER INSULATION:PE)  
 +CORSS JACKET PVC,OD:6.2±0.2MM
- 2.CONN.:P1 & P2: 8P8C PLUG,LONG BODY,SINGLE LAY,GOLD PLATED  
 50u".
- 3.ALL BOOT:MOLDING 60P PVC.
- 4.CABLE ASS'Y MUST PASS CONTINUITY TEST.
- 5.MOLD NO:BOOT-03

MERCHANDISE MOQ	EACH 1PCS
LEAD TIME	12 DAY
CABLE MOQ	
CONNECTOR MOQ	

NET MECHANISM Corp  
 www.cabling-ol.net

SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	05/07/10			

TITLE 8P8C PLUG/8P8C PLUG

B	CHANGE MOLD TYPE FOR ASS'Y BOOT	05/07/10
A	INITIAL RELEASE	03/16/06
REV	DESCRIPTION OF CHANGE	DATE

PART NO. C6-YYXXX