



L(MM)	TOLERANCE(MM)
100~499	+15/-0
500~999	+50/-0
1000~4999	+75/-0
5000~14999	+150/-0
15000~49999	+300/-0

C6S-YYXXX
 LENGTH UNIT FT
 COLOR:BL,GY.

PIN OUT:

P1	PAIRS	P2	WIRE COLOR
1	—○—	1	WHITE/ORANGE
2	—○—	2	ORANGE
3	—○—	3	WHITE/GREEN
6	—○—	6	GREEN
5	—○—	5	WHITE/BLUE
4	—○—	4	BLUE
7	—○—	7	WHITE/BROWN
8	—○—	8	BROWN
SHELL	—	SHELL	DRAIN

NOTE:

- CABLE: CAT.6 FTP CABLE.4P*26AWG(7/0.165)(BARE COPPER.INSULATION:HD-PE.OD:0.93±0.05mm)+ CROSS+AL/MY+DRAIN+OUTER JACKET:PVC,OD:5.8±0.2mm
- CONN.:P1,P2 8P8C MODULAR,SHELL SHIELD,LONG BODY,DOUBLE LAY,W/THREE PARTS,GOLD PLATED 50u".
- ASS'Y BOOT:ø6.2mm
- CABLE ASS'Y MUST PASS CONTINUITY TEST.

NET MECHANISM Corp
 www.cabling-ol.net

SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	03/16/06			
TITLE	8P8C PLUG TO 8P8C PLUG			
PART NO.	C6S-YYXXX			