



| L(MM) | TOLERANCE(MM) |
|-------------|---------------|
| 100~499 | +25/-0 |
| 500~999 | +50/-0 |
| 1000~4999 | +75/-0 |
| 5000~14999 | +150/-0 |
| 15000~49999 | +300/-0 |

| PIN OUT: | | | |
|----------|-------|-------|--------------|
| P1 | PAIRS | P2 | WIRE COLOR |
| 1 | —○— | 1 | WHITE/ORANGE |
| 2 | —○— | 2 | ORANGE |
| 3 | —○— | 3 | WHITE/GREEN |
| 6 | —○— | 6 | GREEN |
| 5 | —○— | 5 | WHITE/BLUE |
| 4 | —○— | 4 | BLUE |
| 7 | —○— | 7 | WHITE/BROWN |
| 8 | —○— | 8 | BROWN |
| SHELL | — | SHELL | DRAIN |

C6S-YYXXX
 ——— LENGTH UNIT FT
 ——— COLOR:BL,GY.

NOTE:

- 1.CABLE: CAT.6 FTP CABLE.4P*26AWG(7/0.165)(BARE COPPER).
 INSULATION:HD-PE.OD:0.93±0.05mm)+CROSS+AL/MY+
 DRAIN+OUTER JACKET:PVC,OD:5.8~6.0±0.2mm
- 2.CONN.:P1,P2 8P8C MODULAR,SHELL SHIELD,LONG BODY,DOUBLE
 LAY,W/THREE PARTS,GOLD PLATED 50u”.
- 3.ALL BOOT:MOLDING 60P PVC.
- 4.CABLE ASS’Y MUST PASS CONTINUITY TEST.
- 5.MOLD NO:BOOT-03

| | |
|-----------------|-----------|
| MERCHANDISE MOQ | EACH 1PCS |
| LEAD TIME | 12 DAY |
| CABLE MOQ | |
| CONNECTOR MOQ | |

NET MECHANISM Corp
 www.cabling-ol.net

| | | | | |
|-------|----------|---------|-----|---|
| SCALE | NONE | | REV | C |
| UNIT | MM | | | |
| SHEET | 1/1 | DWG NO. | | |
| DATE | 11/18/13 | | | |

| | |
|----------|---------------------|
| TITLE | 8P8C PLUG/8P8C PLUG |
| PART NO. | C6S-YYXXX |

| | | |
|-----|---------------------------------|----------|
| C | CHANGING DIMENSION TOLERANCE | 11/18/13 |
| B | CHANGE MOLD TYPE FOR ASS’Y BOOT | 05/07/10 |
| A | INITIAL RELEASE | 03/16/06 |
| REV | DESCRIPTION OF CHANGE | DATE |