



L(MM)	TOLERANCE(MM)
100~499	+15/-0
500~999	+50/-0
1000~4999	+75/-0
5000~14999	+150/-0
15000~49999	+300/-0

PIN OUT:			
P1	PAIRS	P2	WIRE COLOR
1	—○—	1	WHITE/ORANGE
2	—○—	2	ORANGE
3	—○—	3	WHITE/GREEN
6	—○—	6	GREEN
5	—○—	5	WHITE/BLUE
4	—○—	4	BLUE
7	—○—	7	WHITE/BROWN
8	—○—	8	BROWN
SHELL	—	SHELL	DRAIN

C6S-YYXXX
 ——— LENGTH UNIT FT
 ——— COLOR:BL,GY.

- NOTE:
- 1.CABLE: CAT.6 FTP CABLE.4P*26AWG(7/0.165)(BARE COPPER. INSULATION:HD-PE.OD:0.93±0.05mm)+CROSS+AL/MY+ DRAIN+OUTER JACKET:PVC,OD:5.8±0.2mm
 - 2.CONN.:P1,P2 8P8C MODULAR,SHELL SHIELD,LONG BODY,DOUBLE LAY,W/THREE PARTS,GOLD PLATED 50u”.
 - 3.ALL BOOT:MOLDING 60P PVC.
 - 4.CABLE ASS’Y MUST PASS CONTINUITY TEST.
 - 5.MOLD NO:BOOT-03

MERCHANDISE MOQ	EACH 1PCS		
LEAD TIME	12 DAY		
CABLE MOQ			
CONNECTOR MOQ			
NET MECHANISM Corp www.cabling-ol.net			
SCALE	NONE		REV B
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	05/07/10		
TITLE	8P8C PLUG/8P8C PLUG		
PART NO.	C6S-YYXXX		

B	CHANGE MOLD TYPE FOR ASS’Y BOOT	05/07/10
A	INITIAL RELEASE	03/16/06
REV	DESCRIPTION OF CHANGE	DATE