



P/N	L (MM)	T (MM)
C7S-PM005	500	+50/-0
C7S-PM010	1000	+75/-0
C7S-PM020	2000	+75/-0
C7S-PM030	3000	+75/-0
C7S-PM050	5000	+150/-0
C7S-PM075	7500	+150/-0
C7S-PM100	10000	+150/-0
C7S-PM150	15000	+300/-0

PIN OUT:			
P1	PAIRS	P2	WIRE COLOR
1	○	1	WHITE
2	○	2	ORANGE
3	○	3	WHITE
6	○	6	LIGHT GREEN
5	○	5	WHITE
4	○	4	LIGHT BLUE
7	○	7	WHITE
8	○	8	BROWN
SHELL	—	SHELL	DRAIN

NOTE:

- CABLE: CAT.7 S-STP CABLE. 4P\*30AWG (7/0.1) (BARE COPPER. INSULATION: HD-PE. OD:0.93±0.05mm)+ AL/MY+DRAIN+OUTER JACKET: PURPLE PVC, OD: ø5.4±0.2mm
- CONN.: P1,P2 8P8C MODULAR, SHELL SHIELD, LONG BODY, SINGLE LAY, W/THREE PARTS, GOLD PLATED 50u", GOLD PLATED SHELL.
- ALL HOOD: MOLDED 90P PURPLE PVC.
- CABLE ASS'Y MUST PASS CONTINUITY TEST.
- MOLD NO.: 88-05.

NET MECHANISM Corp  
www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	07/11/07			
TITLE				
8P8C PLUG TO 8P8C PLUG				
PART NO.				
C7S-PMXXX				