

P/N	X(M)	L(MM)	TOLERANCE(MM)
D15PS-M0050-CC	0.5	500	+50/-0
D15PS-M0100-CC	1	1000	+75/-0
D15PS-M0150-CC	1.5	1500	+75/-0
D15PS-M0200-CC	2	2000	+75/-0
D15PS-M0250-CC	2.5	2500	+75/-0
D15PS-M0300-CC	3	3000	+75/-0
D15PS-M0400-CC	4	4000	+75/-0
D15PS-M0500-CC	5	5000	+150/-0
D15PS-M1000-CC	10	10000	+150/-0


NOTE:

- CABLE:UL2464 28AWG X 8P+AL/MY+DRAIN+BRAID,PVC JACKET, COLOR:BEIGE(BG02), $\phi 7.0 \pm 0.15$ mm.
- CONN.:P1:D-SUB 15PIN MALE: SOLDER TYPE,BLACK PBT INSULATION, GOLD FLASH CONTACTS,SHELL NICKEL PLATED ON TOP AND TIN PLATED ON BOTTEM.
P2:D-SUB 15PIN FEMALE:SOLDER TYPE,BLACK PBT INSULATION, GOLD FLASH CONTACTS,SHELL NICKEL PLATED ON TOP AND TIN PLATED ON BOTTEM.
- $\phi 1.0 \times 10$ mm BLACK HEAT SHRINK TUBING.
- $\phi 10.0 \times 15$ mm BLACK HEAT SHRINK TUBING.
- $\phi 1.5 \times 20$ mm BLACK HEAT SHRINK TUBING.
- D-SUB 15P HOOD.
- TESTING:100% ELECTRICAL TEST.
- PACKING:EACH CABLE IN A POLY-BAG.

PIN OUT:



NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	C
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/05/13			
TITLE				
DB15M TO DB15F				
PART NO.				
D15PS-MXXXX-CC				