



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
D9P-F0025-EG	0.25	250	+15/-0
D9P-F0050-EG	0.5	500	+50/-0
D9P-F0075-EG	0.75	750	+50/-0
D9P-F0100-EG	1	1000	+75/-0
D9P-F0150-EG	1.5	1500	+75/-0
D9P-F0200-EG	2	2000	+75/-0
D9P-F0300-EG	3	3000	+75/-0

PIN OUT :

- P1 OPEN
- 1 RD
- 2 _____
- _____
- _____
- _____
- 9 _____

NOTE:
 1.CABLE:UL2651 28AWG*9C P=1.27MM, GRAY PVC FLAT CABLE.
 2.CONN:P1 DB9M, IDC TYPE, WITH JACK #4-40 SCREW, PIN:G/F, INSULATION BLACK.
 3.M2.6 HEX NUT.
 4.TESTING:100% ELECTRICAL TEST.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	07/21/05	TITLE		
		IDC DB9M TO OPEN		
PART NO.		D9P-FXXXX-EG		