


P/N	X(M)	L(MM)	TOLERANCE(MM)
D9P-M0050-CG	0.5	500	+50/-0
D9P-M0100-CG	1	1000	+75/-0
D9P-M0150-CG	1.5	1500	+75/-0
D9P-M0200-CG	2	2000	+75/-0
D9P-M0250-CG	2.5	2500	+75/-0
D9P-M0300-CG	3	3000	+75/-0
D9P-M0400-CG	4	4000	+75/-0
D9P-M0500-CG	5	5000	+150/-0
D9P-M1000-CG	10	10000	+150/-0

PIN OUT:



SHELL ————— DRAIN+BRAID

NOTE:

- 1.CABLE:UL2464 28AWG X 5P+AL/MY+DRAIN+BRAID,PVC JACKET, COLOR:BEIGE(BG-02), $\phi 6.0 \pm 0.15$ mm.
- 2.CONN.:P1:D-SUB 9PIN MALE: SOLDER TYPE,BLACK PBT INSULATION, GOLD FLASH CONTACTS,SHELL NICKEL PLATED ON TOP AND TIN PLATED ON BOTTOM.
3. $\phi 1.0 \times 10$ MM BLACK HEAT SHRINK TUBING.
4. $\phi 7.0 \times 15$ MM BLACK HEAT SHRINK TUBING.
5. $\phi 1.5 \times 30$ MM BLACK HEAT SHRINK TUBING.
- 6.D-SUB 9P HOOD.
- 7.TESTING:100% ELECTRICAL TEST.
- 8.PACKING:EACH CABLE IN A POLY-BAG.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	07/02/08			
TITLE		DB9M TO OPEN		
PART NO.		D9P-MXXXX-CG		