


CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
D9PS-F0025-FF	0.25	250	+15/-0
D9PS-F0050-FF	0.5	500	+50/-0
D9PS-F0075-FF	0.75	750	+50/-0
D9PS-F0100-FF	1	1000	+75/-0
D9PS-F0150-FF	1.5	1500	+75/-0
D9PS-F0200-FF	2	2000	+75/-0
D9PS-F0300-FF	3	3000	+75/-0

PIN OUT :



NOTE:

- 1.CABLE:UL2651 28AWG*9C P=1.27MM, GRAY PVC FLAT CABLE.
- 2.CONN:P1 DB9M, IDC TYPE, WITH JACK #4-40 SCREW, PIN:G/F, INSULATION BLACK.
P2 DB9F, IDC TYPE, WITH JACK #4-40 SCREW, PIN:G/F, INSULATION BLACK.
- 3.#4-40 HEX NUT.
- 4.TESTING:100% ELECTRICAL TEST.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	07/11/05			
TITLE				
IDC DB9M TO IDC DB9F				
PART NO.				
D9PS-FXXXX-FF				