



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
D9PS-F0025-FF	0.25	250	+25/-0
D9PS-F0050-FF	0.5	500	+50/-0
D9PS-F0075-FF	0.75	750	+50/-0
D9PS-F0100-FF	1	1000	+75/-0
D9PS-F0150-FF	1.5	1500	+75/-0
D9PS-F0200-FF	2	2000	+75/-0
D9PS-F0300-FF	3	3000	+75/-0

PIN OUT :

P1		P2
1	RD	1
2		2
•		•
•		•
•		•
9		9

NOTE:

- CABLE:UL2651 28AWG*9C P=1.27MM, GRAY PVC FLAT CABLE.
- CONN:P1 DB9M, IDC TYPE, WITH JACK #4-40 SCREW, PIN:G/F, INSULATION BLACK.
P2 DB9F, IDC TYPE, WITH JACK #4-40 SCREW, PIN:G/F, INSULATION BLACK.
- #4-40 HEX NUT.
- TESTING:100% ELECTRICAL TEST.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/05/13			
TITLE				
IDC DB9M TO IDC DB9F				
PART NO.				
D9PS-FXXXX-FF				