



WIRE CONNECTION

P1	P2 COLOR	P1	P2 COLOR
1	12 WHITE	10	3 WHITE
3	10 BROWN	12	1 BLUE
2	11 DRAIN	11	2 DRAIN
4	9 WHITE	13	13 WHITE
6	7 RED	14	14 RED
5	8 DRAIN	15	15 WHITE
7	6 WHITE	17	17 BLACK
9	4 GREEN	16	16 DRAIN
8	5 DRAIN	18	18 YELLOW
		19	19 ORANGE
		SHELL	SHELL DRAIN

NOTE:

- 1.CABLE:UL20276 (28AWG*1P+D-AL-MYLAR)*5C+28AWG*4C+AL/MY +DRAIN(BARE COPPER)+BRAID(A-M ALLOY),PVC JACKET BLACK, OD:7.3±0.15mm.
- 2.CONNECTOR:P1,P2:DISPLAYPORT 20P MALE, GOLD PLATED CONTACTS, INSULATION:BLACK, NICKEL PLATED SHELL, ASSEMBLY TYPE.
- 3.DISPLAYPORT BLACK HOOD.
- 4.SR MOLDING BLACK PVC.
- 5.MOLD NO.: DISPLAYPORT-N01,DISPLAYPORT-SR.
- 6.100% OPEN AND SHORT TESTING.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	10/18/10			
TITLE DISPLAYPORT TO DISPLAYPORT				
PART NO. DDIS-DPMDPM-MXX				

P/N	L(MM)	T(MM)
DDIS-DPMDPM-M005	500	+50/-0
DDIS-DPMDPM-M01	1000	+75/-0
DDIS-DPMDPM-M02	2000	+75/-0
DDIS-DPMDPM-M03	3000	+75/-0