


P/N	XX(FT)	L(MM)	TOLERANCE(MM)
DDIS-IMIF-06	06	1829	+75/-0
DDIS-IMIF-10	10	3048	+75/-0
DDIS-IMIF-15	15	4572	+75/-0

NOTE:

- CABLE:UL20276 (30AWG+SP+AL/MY)*3COAX+(28AWG*1P+D+AL/MY)*7PCS+28AWG*1P+28AWG*5C+AL/MY+DRAIN(BARE COPPER)+BRAID (A-M ALLOY) PVC JACKET BLACK,OD:9.0±0.15mm.
- CONN:P1 DVI 24+5 MALE,PIN:G/F,INSULATION BLACK,GOLD PLATED SHELL.
P2 DVI 24+5 FEMALE,PIN:G/F,INSULATION WHITE ASS'Y TYPE,GOLD PLATED SHELL.
- SCREW:#4-40UNC MOLDED BLACK.
- P1 HOOD MOLDED 45P PVC BLACK.
- 100% ELECTRICAL TESTING.

WIRE LIST:

P1		P2	P1		P2	P1		P2
1	BROWN	1	17	YELLOW	17	C1	RED COAX	C1
2	WHITE	2	18	WHITE	18	C2	GREEN COAX	C2
3	D.W	3	19	D.W	19	C3	BLUE COAX	C3
4	GREEN	4	20	WHITE	20	C5	SP	C5
5	WHITE	5	21	ORANGE	21	C4	GREEN	C4
6	ORANGE	6	22	D.W	22	SHELL	DRAIN	SHELL
7	YELLOW	7	23	WHITE	23			
8	BLACK	8	24	BLACK	24			
9	RED	9						
10	WHITE	10						
11	D.W	11						
12	BLUE	12						
13	WHITE	13						
14	BROWN	14						
15	RED	15						
16	WHITE	16						

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	12/20/10	TITLE		
		DVI 24+5 MALE TO DVI 24+5 FEMALE		
PART NO.		DDIS-IMIF-XX		