



WIRE LIST:

P1	1	BROWN	P2	1	YELLOW
	2	WHITE		2	WHITE
	3	D.W		3	D.W
	4	GREEN		4	WHITE
	5	WHITE		5	ORANGE
	6	ORANGE		6	YELLOW
	7	YELLOW		7	BLACK
	8	BLACK		8	RED
	9	RED		9	WHITE
	10	WHITE		10	D.W
	11	D.W		11	BLUE
	12	BLUE		12	WHITE
	13	WHITE		13	BROWN
	14	BROWN		14	RED
	15	RED		15	WHITE
	16	WHITE		16	SHELL
					DRAIN
					SHELL
					RED COAX
					GREEN COAX
					BLUE COAX
					SP
					GREEN

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
DDIS-IMIM-06	06	1829	+75/-0
DDIS-IMIM-10	10	3048	+75/-0
DDIS-IMIM-15	15	4572	+75/-0

NOTE:

- CABLE:UL20276 (30AWG+SP+AL/MY)\*3COAX+(28AWG\*1P+D+AL/MY)\*7PCS +28AWG\*1P+28AWG\*5C++AL/MY+DRAIN(BARE COPPER)+BRAID(A-M ALLOY) PVC JACKET BLACK,OD:9.0±0.15mm
- CONN:P1 & P2 DVI 24+5 MALE,PIN:G/F,INSULATION BLACK,GOLD PLATED SHELL.
- SCREW:#4-40UNC MOLDED BLACK.
- HOOD MOLDED 45P PVC BLACK.
- TEST: 100% ELECTRICAL TESTING.
- MOLD NO.: DVI-01.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	12/20/10			
TITLE DVI 24+5 MALE TO DVI 24+5 MALE				
PART NO. DDIS-IMIM-XX				