



WIRE LIST:

P1	1	BROWN	P2	1	YELLOW
	2	WHITE		2	WHITE
	3	D.W		3	D.W
	4	GREEN		4	WHITE
	5	WHITE		5	ORANGE
	6	ORANGE		6	D.W
	7	YELLOW		7	WHITE
	8	BLACK		8	BLACK
	9	RED		9	RED COAX
	10	WHITE		10	GREEN COAX
	11	D.W		11	BLUE COAX
	12	BLUE		12	SP
	13	WHITE		13	GREEN
	14	BROWN		14	SHELL
	15	RED		15	DRAIN
	16	WHITE		16	SHELL

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
DDIS-IMIM-06	06	1829	+75/-0
DDIS-IMIM-10	10	3048	+75/-0
DDIS-IMIM-15	15	4572	+75/-0

NOTE:

- CABLE:UL20276 (30AWG+SP+AL/MY)\*3COAX+(28AWG\*1P+D+AL/MY)\*7PCS +28AWG\*1P+28AWG\*5C++AL/MY+DRAIN(BARE COPPER)+BRAID(A-M ALLOY) PVC JACKET BLACK,OD:9.0±0.15mm
- CONN:P1 & P2 DVI 24+5 MALE,PIN:G/F,INSULATION BLACK,GOLD PLATED SHELL.
- SCREW:#4-40UNC MOLDED BLACK.
- HOOD MOLDED 45P PVC BLACK.
- TEST: 100% ELECTRICAL TESTING.
- MOLD NO.: DVI-01.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	12/20/10			
TITLE DVI 24+5 MALE TO DVI 24+5 MALE				
PART NO. DDIS-IMIM-XX				