



NOTE:

- CABLE:UL20276(28AWG*1P+D+AL/MY)*4PCS +28AWG*1P+28AWG*3C++AL/MY+DRAIN (BARE COPPER)+BRAID(A-M ALLOY),PVC JACKET BLACK OD:7.0±0.15MM
- CONN:P1 & P2 DVI 18+1 SOLDER TYPE MALE, PIN:G/F,INSULATION BLACK,SHELL GOLD PLATED ON TOP AND TIN PLATED ON BOTTOM.
- SCREW:#4-40UNC MOLDED WHITE.
- HOOD MOLDED 45P PVC WHITE.
- MOLD P/N:DVI-01.

WIRE LIST:

P1		P2	P1	P2	P1	P2
1	BROWN	1	14	RED	22	D.W
2	WHITE	2	15	PURPLE	23	WHITE
3	D.W	3	16	WHITE	24	BLUE
6	ORANGE	6	17	GREEN		
7	YELLOW	7	18	WHITE	SHELL	DRAIN
9	RED	9	19	D.W		SHELL
10	WHITE	10				
11	D.W	11				

CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
DDIS-SDMSDM-03	03	914	+50/-0
DDIS-SDMSDM-06	06	1829	+75/-0
DDIS-SDMSDM-10	10	3048	+75/-0
DDIS-SDMSDM-15	15	4572	+75/-0

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	10/08/10	TITLE		
		DVI 18+1M TO DVI 18+1M		
PART NO.		DDIS-SDMSDM-XX		