



PIN OUT

NOTE:

1. CABLE: 28AWG X 15C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (BG-03) PVC JACKET $\phi 6.0 \pm 0.15\text{mm}$
2. CONNECTOR: P1 & P2: HIGH DENSITY D-SUB 15PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS.
3. THUMB SCREW TO BE MOLDED.
4. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
5. ALL HOOD: MOLDED BEIGE(BG-03) PVC.
6. TESTING:100% ELECTRICAL TESTING.

P1	P2		P1	P2	
1	1	BLACK	9	9	GRAY
2	2	BROWN	10	10	WHITE
3	3	RED	11	11	PINK
4	4	ORANGE	12	12	LIGHT GREEN
5	5	YELLOW	13	13	BLACK/WHITE
6	6	GREEN	14	14	BROWN/WHITE
7	7	BLUE	15	15	RED/WHITE
8	8	PURPLE	SHELL	SHELL	(DRAIN WIRE)

CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
DIS-HD15MM-03	03	914	+50/-0
DIS-HD15MM-06	06	1829	+75/-0
DIS-HD15MM-10	10	3048	+75/-0
DIS-HD15MM-15	15	4572	+75/-0

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	03/12/07			
TITLE	HDB15M TO HDB15M			
PART NO.	DIS-HD15MM-XX			