



NOTE:

- CABLE1: [(28AWG X 3COAX, EACH COAX SPIRAL SHIELDED, 75 Ω , UL1354) + (24AWG X 4C) + (24AWG X 2PAIRS)], AL-FOIL AND BRAID SHIELDED WITH DRAIN WIRE, UL2919, BLACK PVC JACKET, SLOT OD:9.0 \pm 0.15mm.
CABLE2: NON UL, 26AWG*2C+SPIRAL SHIELD, BLACK PVC JACK, OD:3.0 \pm 0.15mm.
- CONNECTOR:
P1: DIN 14P FEMALE, NICKEL PLATED CONTACTS AND SHELL, SCREW THREAD TYPE.
P2: HIGH DENSITY D-SUB 15PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS, NICKEL PLATED SHELL.
P3: DC3.5mm STEREO PLUG, NICKEL PLATED SHELL.
- SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360 \circ SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
- P1:MOLDED GREEN(GN02) PVC.P2&P3:MOLDED BLACK PVC.
- TESTING: 100% ELECTRICAL TEST .

NET MECHANISM Corp

www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/05/09	TITLE		
		DIN14F TO HDB15M+3.5STEREO PLUG		
PART NO.		EDIS-15M35M-D14F-MXX		