


PIN OUT		
D14F	HD15M	
1	1	RED(COAX)
6	6	RED(SPIRAL)
2	2	GREEN(COAX)
7	7	GREEN(SPIRAL)
3	3	BLUE(COAX)
8	8	BLUE(SPIRAL)
4	4	BLACK
RED 1	5	BROWN
	11	YELLOW
	12	PURPLE
WHITE 2	10	ORANGE
	13	ORANGE/BLACK
	14	BLUE
	9	BLUE/WHITE
SPIRAL SHELL	SHELL	SHELL(DRAIN + BRAD)

NOTE:

- CABLE1: [(28AWG X 3COAX, EACH COAX SPIRAL SHIELDED, 75 Ω , UL1354) + (24AWG X 4C) + (24AWG X 2PAIRS)], AL-FOL AND BRAD SHIELDED WITH DRAIN WIRE, UL2919, BLACK PVC JACKET, SLOT 00-9.0 \pm 0.15mm.
CABLE2: NON UL, 28AWG*2C+SPIRAL SHIELD, BLACK PVC JACK, 003.0 \pm 0.15mm.
- CONNECTOR:
P1: DIN 14P FEMALE, NICKEL PLATED CONTACTS AND SHELL, SCREW THREAD TYPE.
P2: HIGH DENSITY D-SUB 15PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS, NICKEL PLATED SHELL.
P3: DC3.5mm STEREO PLUG, NICKEL PLATED SHELL.
- SHIELDED: COPPER FOL TAPE COVER PREMOLDED AND 360 SOLDER TO CONNECTOR SHELL AND CABLE BRAD.
- P1:MOLDED GREEN(CN2) PVC.P2&P3:MOLDED BLACK PVC.
- TESTING: 100% ELECTRICAL TEST .

NET MECHANISM Corp

www.cobling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/05/09			
TITLE				
DIN14F TO HD15M+3.5STEREO PLUG				
PART NO.				
EDIS-15M35M-D14F-MXX				