



- NOTE:
- CABLE: [(28AWG X 3COAX, EACH COAX SPIRAL SHIELDED, 75Ω, UL1354) + (28AWG X 4C) + (28AWG X 2PAIRS)], AL-FOIL AND BRAID(65% A-MALLOY) SHIELDED WITH DRAIN WIRE(BARE COPPER), UL2919,BLACK PVC JACKET, SLOT $\varnothing 9.0 \pm 0.15$ mm.
 - CONNECTOR: 1: DIN 14 MALE: NICKEL PLATED CONTACTS AND SHELL,LOCKER TYPE.
2: HIGH DENSITY D-SUB 15PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS, 9PIN UNLOADED. NICKEL PLATED SHELL.
 - THUMB SCREW TO BE MOLDED BLACK.
 - SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE DRAIN.
 - ALL HOOD: MOLDED BLACK(BK-02) PVC.
 - TESTING: 100% ELECTRICAL TEST.
 - PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
 - MOLD NO.: D14M-N01, D14M-02, HD15-N01,HD15-01,02,03.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/30/10			
TITLE		DIN 14/M TO HDB 15/M		
PART NO.		EDIS-HD15MD14M-M005		