


P/N	L(MM)	T(MM)
EDIS-HD15MDIN14F-M01	1000	+75/-0
EDIS-HD15MDIN14F-M03	3000	+75/-0
EDIS-HD15MDIN14F-M05	5000	+150/-0
EDIS-HD15MDIN14F-M10	10000	+150/-0
EDIS-HD15MDIN14F-M20	20000	+300/-0
EDIS-HD15MDIN14F-M30	30000	+300/-0
EDIS-HD15MDIN14F-M50	50000	+500/-0



NOTE:

- CABLE: [(28AWG X 3COAX, EACH COAX SPIRAL SHIELDED, 75Ω, UL1354)+(24AWG X 4C)+(24AWG X 2PAIRS)], AL-FOIL AND BRAID(85% min) SHIELDED WITH DRAIN WIRE, UL2919, BLACK PVC JACKET, SLOT $\phi 9.0 \pm 0.15$ mm.
- CONNECTOR: 1: DIN 14P FEMALE, NICKEL PLATED CONTACTS AND SHELL, SCREW THREAD TYPE.
2: HIGH DENSITY D-SUB 15PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS, 9PIN UNLOADED. NICKEL PLATED SHELL.
- THUMB SCREW TO BE MOLDED BLACK.
- SHIELDED: COPPER FOIL TAPE COVER PREMOLD AND 360° SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
- ALL HOOD: MOLDED BLACK(BK-02) PVC.
- TESTING: 100% ELECTRICAL TEST .
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.
- MOLD NO.: D14F-N01, D14F-02, HD15-N01, HD15-01, 02, 03.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	12/21/06			
TITLE		DIN 14/F TO HDB 15/M		
PART NO.		EDIS-HD15MDIN14F-MXX		