



PIN OUT:

P/N	x(M)	L(MM)	TOLERANCE(MM)
FCN24S-B0100	1	1000	+25/-0
FCN24S-B0200	2	2000	+50/-0
FCN24S-B0300	3	3000	+50/-0
FCN24S-B0500	5	5000	+50/-0

A1	RED	P2	OPEN	B3	GRAY	P2	OPEN
A2	GRAY	P2	OPEN	B4	GRAY	P2	OPEN
A3	GRAY	P2	OPEN	B5	GRAY	P2	OPEN
A4	GRAY	P2	OPEN	B6	GRAY	P2	OPEN
A5	GRAY	P2	OPEN	B7	GRAY	P2	OPEN
A6	GRAY	P2	OPEN	B8	GRAY	P2	OPEN
A7	GRAY	P2	OPEN	B9	GRAY	P2	OPEN
A8	GRAY	P2	OPEN	B10	GRAY	P2	OPEN
A9	GRAY	P2	OPEN	B11	GRAY	P2	OPEN
A10	GRAY	P2	OPEN	B12	GRAY	P2	OPEN
A11	GRAY	P2	OPEN				
A12	GRAY	P2	OPEN				
B1	GRAY	P2	OPEN				
B2	GRAY	P2	OPEN				

REMARK

- 1.CABLE:UL1007 28AWG,JACKET BLUE,OD=1.2MM.
- 2.CONN: FUJITSU P/N:FCN-367J024-AU-F.
- 3.HOT PACK TYPE PE FILM.
- 4.EACH CABLE IN A ZIP PE-BAG.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04	TITLE		
		24P IDC TO OPEN		
PART NO.		FCN24S-BXXXX		