



PIN OUT:

P/N	x(M)	L(MM)	TOLERANCE(MM)
FCN24S-B0100	1	1000	+25/-0
FCN24S-B0200	2	2000	+50/-0
FCN24S-B0300	3	3000	+50/-0
FCN24S-B0500	5	5000	+50/-0

P1	A1	RED	P2	B3	GRAY	OPEN
	A2	GRAY		B4	GRAY	OPEN
	A3	GRAY		B5	GRAY	OPEN
	A4	GRAY		B6	GRAY	OPEN
	A5	GRAY		B7	GRAY	OPEN
	A6	GRAY		B8	GRAY	OPEN
	A7	GRAY		B9	GRAY	OPEN
	A8	GRAY		B10	GRAY	OPEN
	A9	GRAY		B11	GRAY	OPEN
	A10	GRAY		B12	GRAY	OPEN
	A11	GRAY				
	A12	GRAY				
	B1	GRAY				
	B2	GRAY				

REMARK

- 1.CABLE:UL1007 28AWG,JACKET BLUE,OD=1.2MM.
- 2.CONN: FUJITSU P/N:FCN-367J024-AU-F.
- 3.HOT PACK TYPE PE FILM.
- 4.EACH CABLE IN A ZIP PE-BAG.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04	TITLE		
		24P IDC TO OPEN		
PART NO.		FCN24S-BXXXX		