



P/N	X(M)	L(MM)	TOLERANCE(MM)
FCN24S-F0025	0.25	250	+25/-0
FCN24S-F0050	0.5	500	+25/-0
FCN24S-F0075	0.75	750	+25/-0
FCN24S-F0100	1	1000	+25/-0
FCN24S-F0150	1.5	1500	+50/-0
FCN24S-F0200	2	2000	+50/-0
FCN24S-F0300	3	3000	+50/-0

PIN OUT:

P1		P2	
A1	RED	OPEN	
A2	GRAY	OPEN	
A3	GRAY	OPEN	
A4	GRAY	OPEN	
A5	GRAY	OPEN	
A6	GRAY	OPEN	
A7	GRAY	OPEN	
A8	GRAY	OPEN	
A9	GRAY	OPEN	
A10	GRAY	OPEN	
A11	GRAY	OPEN	
A12	GRAY	OPEN	
B1	GRAY	OPEN	
B2	GRAY	OPEN	
P1		P2	
B3	GRAY	OPEN	
B4	GRAY	OPEN	
B5	GRAY	OPEN	
B6	GRAY	OPEN	
B7	GRAY	OPEN	
B8	GRAY	OPEN	
B9	GRAY	OPEN	
B10	GRAY	OPEN	
B11	GRAY	OPEN	
B12	GRAY	OPEN	

REMARK

- 1.CABLE:UL 2651 28AWG(7/0.127)*24C,105°C 300V,COLOR:GRAY.
- 2.P1 CONN.:FUJITSU P/N:FCN-367J024-AU-F.
- 3.THE CABLE SHALL BE 100% ELECTRICAL TEST.

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE FCN 24P FEMALE IDC TO OPEN				
PART NO. FCN24S-FXXXX				