



P/N	X(M)	L(MM)	TOLERANCE(MM)
FCN24SS-M0050	0.5	500	+25/-0
FCN24SS-M0100	1	1000	+25/-0
FCN24SS-M0150	1.5	1500	+50/-0
FCN24SS-M0200	2	2000	+50/-0
FCN24SS-M0300	3	3000	+50/-0
FCN24SS-M0500	5	5000	+50/-0

PIN OUT :

P1		P2	P1		P2
A1	0	BLACK	A1	0	PURPLE
B1	0	BLACK/WHITE	A8	0	PURPLE/WHITE
A2	0	BROWN	B1	0	GRAY
B2	0	BROWN/WHITE	A2	0	GRAY/BLACK
A3	0	RED	B2	0	WHITE
B3	0	RED/WHITE	A3	0	ORANGE/BLACK
A4	0	ORANGE	B3	0	B10
B4	0	ORANGE/WHITE	A4	0	PINK
A5	0	YELLOW	A11	0	RED/BLACK
B5	0	YELLOW/BLACK	B4	0	B11
A6	0	GYEEN	A5	0	LIGHT GREEN
B6	0	GREEN/WHITE	A12	0	GREEN/BLACK
A7	0	BLUE	B5	0	B12
B7	0	BLUE/WHITE	A6	0	GND
			B6	0	BRAID+DRAIN
			A7	0	GND
			B7	0	

REMARK

- 1.CABLE:UL2464 28AWG*12P(ID=0.85)+AL+D+B+PVC
JACKET:BEIGE(BG-02),OD=8.5±0.15MM.
- 2.CONN.: FUJITSU P/N:FCN-361J024-AU AND FCN-360C024-B.
- 3.WIRE:UL1007 16AWG GREEN ø2.4MM.
- 4.TERMINAL:Y TYPE TERMINAL,COPPER TINNED PLATED.
- 5.TUBE:HEAT SHRINKING TUBE BLACK ø10.0*40MM.
- 6.EACH CABLE IN A ZIP PE-BAG.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	10/15/04			
TITLE				
FCN 24P FEMALE SOLDER TYPE/B.E.				
PART NO.				
FCN24SS-MXXXX				