



P/N	X(M)	L(MM)	TOLERANCE(MM)
FCN40S-B0100	1	1000	+25/-0
FCN40S-B0200	2	2000	+50/-0
FCN40S-B0300	3	3000	+50/-0
FCN40S-B0500	5	5000	+50/-0

PIN OUT:

P1	_____	P2	_____	P1	_____	P2	_____	P1	_____	P2	_____
A1	_____	OPEN	A15	_____	OPEN	B9	_____	OPEN	B9	_____	OPEN
A2	_____	OPEN	A16	_____	OPEN	B10	_____	OPEN	B10	_____	OPEN
A3	_____	OPEN	A17	_____	OPEN	B11	_____	OPEN	B11	_____	OPEN
A4	_____	OPEN	A18	_____	OPEN	B12	_____	OPEN	B12	_____	OPEN
A5	_____	OPEN	A19	_____	OPEN	B13	_____	OPEN	B13	_____	OPEN
A6	_____	OPEN	A20	_____	OPEN	B14	_____	OPEN	B14	_____	OPEN
A7	_____	OPEN	B1	_____	OPEN	B15	_____	OPEN	B15	_____	OPEN
A8	_____	OPEN	B2	_____	OPEN	B16	_____	OPEN	B16	_____	OPEN
A9	_____	OPEN	B3	_____	OPEN	B17	_____	OPEN	B17	_____	OPEN
A10	_____	OPEN	B4	_____	OPEN	B18	_____	OPEN	B18	_____	OPEN
A11	_____	OPEN	B5	_____	OPEN	B19	_____	OPEN	B19	_____	OPEN
A12	_____	OPEN	B6	_____	OPEN	B20	_____	OPEN	B20	_____	OPEN
A13	_____	OPEN	B7	_____	OPEN						
A14	_____	OPEN	B8	_____	OPEN						

- REMARK
- 1.CABLE:UL1007 28AWG,JACKET BLUE,OD=1.2MM.
 - 2.CONN: FUJITSU P/N:FCN-367J040-AU-F.
 - 3.HOT PACK TYPE PE FILM.
 - 4.EACH CABLE IN A ZIP PE-BAG.

NET MECHANISM Corp					
www.cabling-ol.net					
SCALE	NONE		REV	A	
UNIT	MM				
SHEET	1/1	DWG NO.			
DATE	05/11/05	TITLE			
		40P IDC TO OPEN			
		PART NO.			
		FCN40S-BXXXX			