



PIN OUT:

P1	RED	P2	OPEN	P1	GRAY	P2	OPEN	P1	GRAY	P2	OPEN
A1	GRAY	OPEN	A15	GRAY	OPEN	B9	GRAY	OPEN	B9	GRAY	OPEN
A2	GRAY	OPEN	A16	GRAY	OPEN	B10	GRAY	OPEN	B10	GRAY	OPEN
A3	GRAY	OPEN	A17	GRAY	OPEN	B11	GRAY	OPEN	B11	GRAY	OPEN
A4	GRAY	OPEN	A18	GRAY	OPEN	B12	GRAY	OPEN	B12	GRAY	OPEN
A5	GRAY	OPEN	A19	GRAY	OPEN	B13	GRAY	OPEN	B13	GRAY	OPEN
A6	GRAY	OPEN	A20	GRAY	OPEN	B14	GRAY	OPEN	B14	GRAY	OPEN
A7	GRAY	OPEN	B1	GRAY	OPEN	B15	GRAY	OPEN	B15	GRAY	OPEN
A8	GRAY	OPEN	B2	GRAY	OPEN	B16	GRAY	OPEN	B16	GRAY	OPEN
A9	GRAY	OPEN	B3	GRAY	OPEN	B17	GRAY	OPEN	B17	GRAY	OPEN
A10	GRAY	OPEN	B4	GRAY	OPEN	B18	GRAY	OPEN	B18	GRAY	OPEN
A11	GRAY	OPEN	B5	GRAY	OPEN	B19	GRAY	OPEN	B19	GRAY	OPEN
A12	GRAY	OPEN	B6	GRAY	OPEN	B20	GRAY	OPEN	B20	GRAY	OPEN
A13	GRAY	OPEN	B7	GRAY	OPEN						
A14	GRAY	OPEN	B8	GRAY	OPEN						

P/N	X(M)	L(MM)	TOLERANCE(MM)
FCN40S-F0025	0.25	250	+25/-0
FCN40S-F0050	0.5	500	+25/-0
FCN40S-F0075	0.75	750	+25/-0
FCN40S-F0100	1	1000	+25/-0
FCN40S-F0150	1.5	1500	+50/-0
FCN40S-F0200	2	2000	+50/-0
FCN40S-F0300	3	3000	+50/-0
FCN40S-F0500	5	5000	+50/-0

REMARK

- 1.CABLE:UL 2651 28AWG(7/0.127)\*40C,105°C 300V,COLOR:GRAY.
- 2.P1 CONN.:FUJITSU P/N:FCN-367J040-AU-F.
- 3.THE CABLE SHALL BE 100% ELECTRICAL TEST.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	05/11/05			
TITLE				
FCN 40P FEMALE IDC TO OPEN				
PART NO.				
FCN40S-FXXXX				