



PIN OUT:

P1	—	RED	—	P2	P1	—	GRAY	—	P2	P1	—	GRAY	—	P2
A1	—	GRAY	—	A1	A15	—	GRAY	—	A15	B9	—	GRAY	—	B9
A2	—	GRAY	—	A2	A16	—	GRAY	—	A16	B10	—	GRAY	—	B10
A3	—	GRAY	—	A3	A17	—	GRAY	—	A17	B11	—	GRAY	—	B11
A4	—	GRAY	—	A4	A18	—	GRAY	—	A18	B12	—	GRAY	—	B12
A5	—	GRAY	—	A5	A19	—	GRAY	—	A19	B13	—	GRAY	—	B13
A6	—	GRAY	—	A6	A20	—	GRAY	—	A20	B14	—	GRAY	—	B14
A7	—	GRAY	—	A7	B1	—	GRAY	—	B1	B15	—	GRAY	—	B15
A8	—	GRAY	—	A8	B2	—	GRAY	—	B2	B16	—	GRAY	—	B16
A9	—	GRAY	—	A9	B3	—	GRAY	—	B3	B17	—	GRAY	—	B17
A10	—	GRAY	—	A10	B4	—	GRAY	—	B4	B18	—	GRAY	—	B18
A11	—	GRAY	—	A11	B5	—	GRAY	—	B5	B19	—	GRAY	—	B19
A12	—	GRAY	—	A12	B6	—	GRAY	—	B6	B20	—	GRAY	—	B20
A13	—	GRAY	—	A13	B7	—	GRAY	—	B7					
A14	—	GRAY	—	A14	B8	—	GRAY	—	B8					

P/N	X(M)	L(MM)	TOLERANCE(MM)
FCN40SS-F0025	0.25	250	+25/-0
FCN40SS-F0050	0.5	500	+25/-0
FCN40SS-F0075	0.75	750	+25/-0
FCN40SS-F0100	1	1000	+25/-0
FCN40SS-F0150	1.5	1500	+50/-0
FCN40SS-F0200	2	2000	+50/-0
FCN40SS-F0300	3	3000	+50/-0

REMARK

- 1.CABLE:UL 2651 28AWG(7/0.127)*40C,105°C 300V,COLOR:GRAY.
- 2.P1&P2 CONN.:FUJITSU P/N:FCN-367J040-AU-F.
- 3.THE CABLE SHALL BE 100% ELECTRICAL TEST.

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04	TITLE		
		FCN 40P FEMALE IDC TYPE		
PART NO.		FCN40SS-FXXXX		