



PIN OUT:

P/N	X(M)	L(MM)	TOLERANCE(MM)
FCN40SS-M0050	0.5	500	+50/-0
FCN40SS-M0100	1	1000	+75/-0
FCN40SS-M0150	1.5	1500	+75/-0
FCN40SS-M0200	2	2000	+75/-0
FCN40SS-M0300	3	3000	+75/-0
FCN40SS-M0500	5	5000	+150/-0

P1	P2	P1	P2	P1	P2
A1	BLACK	A1	PURPLE	A15	LIGHT BLUE
B1	BLACK/WHITE	B1	PURPLE/WHITE	B15	LIGHT YELLOW
A2	BROWN	A2	GRAY	A16	LIGHT BLUE/BLACK
B2	BROWN/WHITE	B2	GRAY/BLACK	B16	LIGHT BLUE/RED
A3	RED	A3	WHITE	A17	LIGHT BLUE/BLUE
B3	RED/WHITE	B3	ORANGE/BLACK	B17	LIGHT BLUE/GREEN
A4	ORANGE	A4	PINK	A18	GREY/RED
B4	ORANGE/WHITE	B4	RED/BLACK	B18	GREY/GREEN
A5	YELLOW	A5	A12	LIGHT GREEN	A12
B5	YELLOW/BLACK	B5	B12	GREEN/BLACK	B12
A6	GYEEN	A6	A13	PINK/BLACK	A13
B6	GREEN/WHITE	B6	B13	PINK/RED	B13
A7	BLUE	A7	A14	PINK/BLUE	A14
B7	BLUE/WHITE	B7	B14	PINK/GREEN	B14
				A19	BLUE/BLACK
				B19	PURPLE/BLACK
				A20	LIGHT GREEN/BLACK
				B20	LIGHT GREEN/RED
				GND	BRAID+DRAIN
					GND

REMARK

- CABLE:UL2464 28AWG*20P(ID=0.85)+AL+D+B+PVC
JACKET:BEIGE(BG02),OD=9.5±0.15mm
- CONN: FUJITSU P/N:FCN-361J040-AU AND FCN-360C040-B
- WIRE:UL1007 16AWG GREEN ø2.4mm.
- TERMINAL:Y TYPE TERMINAL,COPPER TINNED PLATED.
- TUBE:HEAT SHRINKING TUBE BLACK ø11.0*40mm.
- EACH CABLE IN A ZIP PE-BAG.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	09/27/13			
TITLE				
FCN 40P FEMALE SOLDER TYPE B.E.				
PART NO. FCN40SS-MXXXX				