



P/N	L(MM)	TOLERANCE(MM)
FIS-SMSM-M010	1000	+75/-0
FIS-SMSM-M020	2000	+75/-0
FIS-SMSM-M030	3000	+75/-0
FIS-SMSM-M050	5000	+150/-0
FIS-SMSM-M070	7000	+150/-0
FIS-SMSM-M100	10000	+150/-0

PIN OUT :



NOTE:

1. S-4C-FB CABLE: 20AWG (CONDUCTOR:1/0.813 BARE COPPER)+LD FM PE INSULATION+ AL/MYLAR+BRAID (16*4/0.12) SHIELD, WHITE PVC JACKET, $\phi 6.0 \pm 0.15$ mm.
2. CONN.: P1,P2: F CONN. MALE GOLD FLASH CONTACT. INSULATOR: WHITE GOLD PLATED SHELL (180°).
3. ASS'Y BOOT: PVC 45P WHITE.
4. TESTING: 100% ELECTRICAL TEST.
5. MOLDED NO.: F180-01.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	05/31/07			
TITLE	FM 180° TO FM 180°			
PART NO.	FIS-SMSM-MXXX			