



P/N	X(M)	L(MM)	TOLERANCE(MM)
HPCN20P-M0050	0.5	500	+25/-0
HPCN20P-M0100	1	1000	+25/-0
HPCN20P-M0150	1.5	1500	+50/-0
HPCN20P-M0200	2	2000	+50/-0
HPCN20P-M0300	3	3000	+50/-0
HPCN20P-M0500	5	5000	+50/-0

PIN OUT:

P1		P2
1	YELLOW	OPEN
11	YELLOW/BLACK	OPEN
2	RED	OPEN
12	RED/BLACK	OPEN
3	BROWN	OPEN
13	BROWN/WHITE	OPEN
4	LIGHT BLUE	OPEN
14	LIGHT BLUE/BLACK	OPEN
5	LIGHT BLUE/GREEN	OPEN
15	LIGHT BLUE/YELLOW	OPEN
6	GREEN	OPEN
16	GREEN/BLACK	OPEN
7	BLUE	OPEN
17	BLUE/WHITE	OPEN
8	WHITE	OPEN
18	WHITE/BLACK	OPEN
9	PINK	OPEN
19	PINK/BLACK	OPEN
10	PURPLE	OPEN
20	PURPLE/WHITE	OPEN
SHELL	BRAID+DRAIN	OPEN

NOTE:

- CABLE: 28AWG X 10PAIRS(INSULATION: P.P, CONDUCTOR OD=0.62 ± 0.05mm),AL-FOIL AND BRAID,SHIELDED WITH DRAIN WIRE,UL20276 (IEEE 1284),BEIGE(BG-02) PVC JACKET, MARKING ON PVC JACKET INCLUDE "IEEE 1284-1994 COMPLIANT" ALONG ITS LENGTH. OD=7.0±0.15
- CONNECTOR: P1: HALF PITCH 20PIN CENTRONICS MALE: RIBBON AND IDC ASSY TYPE, GOLD PLATED CONTACTS, W/ABS HOOD.
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.

NET MECHANISM Corp
www.cabling-ol.net

SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE		HPCN20M TO OPEN		
PART NO.		HPCN20P-MXXXX		