



P/N	X(M)	L(MM)	TOLERANCE(MM)
HPCN20PP-M0050	0.5	500	+50/-0
HPCN20PP-M0100	1	1000	+75/-0
HPCN20PP-M0150	1.5	1500	+75/-0
HPCN20PP-M0200	2	2000	+75/-0
HPCN20PP-M0300	3	3000	+75/-0
HPCN20PP-M0500	5	5000	+150/-0

PIN OUT:

P1		P2
1	YELLOW	1
11	YELLOW/BLACK	11
2	RED	2
12	RED/BLACK	12
3	BROWN	3
13	BROWN/WHITE	13
4	LIGHT BLUE	4
14	LIGHT BLUE/BLACK	14
5	LIGHT BLUE/GREEN	5
15	LIGHT BLUE/YELLOW	15
6	GREEN	6
16	GREEN/BLACK	16
7	BLUE	7
17	BLUE/WHITE	17
8	WHITE	8
18	WHITE/BLACK	18
9	PINK	9
19	PINK/BLACK	19
10	PURPLE	10
20	PURPLE/WHITE	20

SHELL ——— BRAID+DRAIN ——— SHELL

- NOTE:
- CABLE: 28AWG*10PAIRS(INSULATION: P.P, CONDUCTOR OD=ø0.62±0.05mm),AL-FOIL AND BRAID,SHIELDED WITH DRAIN WIRE,UL20276 (IEEE 1284),BEIGE(BG02) PVC JACKET, MARKING ON PVC JACKET INCLUDE "IEEE 1284-1994 COMPLIANT" ALONG ITS LENGTH. OD=7.0±0.15
 - CONNECTOR: P1 & P2: HALF PITCH 20PIN CENTRONICS MALE: RIBBON AND IDC ASSY TYPE, GOLD PLATED CONTACTS, W/ABS HOOD.
 - PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.

NET MECHANISM Corp www.cabling-ol.net					
SCALE	NONE		REV	B	
UNIT	MM				
SHEET	1/1	DWG NO.			
DATE	10/26/13				
TITLE HPCN20M TO HPCN20M					
PART NO. HPCN20PP-MXXXX					