



P/N	X(M)	L(MM)	TOLERANCE(MM)
HPCN20PP-M0050	0.5	500	+25/-0
HPCN20PP-M0100	1	1000	+25/-0
HPCN20PP-M0150	1.5	1500	+50/-0
HPCN20PP-M0200	2	2000	+50/-0
HPCN20PP-M0300	3	3000	+50/-0
HPCN20PP-M0500	5	5000	+50/-0

PIN OUT:

P1		P2
1	YELLOW	1
11	YELLOW/BLACK	11
2	RED	2
12	RED/BLACK	12
3	BROWN	3
13	BROWN/WHITE	13
4	LIGHT BLUE	4
14	LIGHT BLUE/BLACK	14
5	LIGHT BLUE/GREEN	5
15	LIGHT BLUE/YELLOW	15
6	GREEN	6
16	GREEN/BLACK	16
7	BLUE	7
17	BLUE/WHITE	17
8	WHITE	8
18	WHITE/BLACK	18
9	PINK	9
19	PINK/BLACK	19
10	PURPLE	10
20	PURPLE/WHITE	20
	BRAID+DRAIN	
SHELL		SHELL

NOTE:

- CABLE: 28AWG X 10PAIRS(INSULATION: P.P, CONDUCTOR OD=ø0.62 ?? 0.05mm)AL-FOIL AND BRAID,SHIELDED WITH DRAIN WIRE,UL20276 (IEEE 1284),BEIGE(BG-02) PVC JACKET, MARKING ON PVC JACKET INCLUDE "IEEE 1284-1994 COMPLIANT" ALONG ITS LENGTH. OD=7.0??0.15
- CONNECTOR: P1 & P2: HALF PITCH 20PIN CENTRONICS MALE: RIBBON AND IDC ASSY TYPE, GOLD PLATED CONTACTS, W/ABS HOOD.
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE				
HPCN20M TO HPCN20M				
PART NO.				
HPCN20PP-MXXXX				