



P/N	X(M)	L(MM)	TOLERANCE(MM)
HPCN36P-M0050	0.5	500	+25/-0
HPCN36P-M0100	1	1000	+25/-0
HPCN36P-M0150	1.5	1500	+50/-0
HPCN36P-M0200	2	2000	+50/-0
HPCN36P-M0300	3	3000	+50/-0
HPCN36P-M0500	5	5000	+50/-0

PIN OUT:

P1		P2(OPEN)		P1		P2(OPEN)
1	YELLOW	OPEN		10	PURPLE	OPEN
19	YELLOW/BLACK	OPEN		28	PURPLE/WHITE	OPEN
2	RED	OPEN		11	GRAY	OPEN
20	RED/BLACK	OPEN		29	GRAY/BLACK	OPEN
3	BROWN	OPEN		12	ORANGE	OPEN
21	BROWN/WHITE	OPEN		30	ORANGE/BLACK	OPEN
4	LIGHT BLUE	OPEN		13	PINK/WHITE	OPEN
22	LIGHT BLUE/BLACK	OPEN		31	PINK/YELLOW	OPEN
5	LIGHT BLUE/GREEN	OPEN		14	GRAY/GREEN	OPEN
23	LIGHT BLUE/YELLOW	OPEN		32	GRAY/YELLOW	OPEN
6	GREEN	OPEN		15	WHITE/YELLOW	OPEN
24	GREEN/BLACK	OPEN		33	WHITE/GREEN	OPEN
7	BLUE	OPEN		16	LIGHT GREEN/RED	OPEN
25	BLUE/WHITE	OPEN		34	GREEN/BLUE	OPEN
8	WHITE	OPEN		17	LIGHT BLUE/BLUE	OPEN
26	WHITE/BLACK	OPEN		35	LIGHT BLUE/RED	OPEN
9	PINK	OPEN		18	PINK/ RED	OPEN
27	PINK/BLACK	OPEN		36	PINK/BLUE	OPEN
				SHELL	BRAID+DRAIN	OPEN

NOTE:

- CABLE: 28AWG X 18PAIRS(INSULATION: P.P, CONDUCTOR OD= $\varnothing 0.62 \pm 0.05\text{mm}$)
AL-FOIL AND BRAID,SHIELDED WITH DRAIN WIRE,UL20276 (IEEE 1284),
BEIGE(BG-02) PVC JACKET, MARKING ON PVC JACKET INCLUDE
"IEEE 1284-1994 COMPLIANT" ALONG ITS LENGTH. OD= 8.0 ± 0.15
- CONNECTOR: P1: HALF PITCH 36PIN CENTRONICS MALE: RIBBON
AND IDC ASSY TYPE, GOLD PLATED CONTACTS, W/ABS HOOD.
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.

NET MECHANISM Corp				
www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE				
HPCN36M TO OPEN				
PART NO.				
HPCN36P-MXXXX				