



P/N	X(M)	L(MM)	TOLERANCE(MM)
HPCN36PP-M0050	0.5	500	+25/-0
HPCN36PP-M0100	1	1000	+25/-0
HPCN36PP-M0150	1.5	1500	+50/-0
HPCN36PP-M0200	2	2000	+50/-0
HPCN36PP-M0300	3	3000	+50/-0
HPCN36PP-M0500	5	5000	+50/-0

PIN OUT:

P1		P2	P1		P2
1	YELLOW	1	10	PURPLE	10
19	YELLOW/BLACK	19	28	PURPLE/WHITE	28
2	RED	2	11	GRAY	11
20	RED/BLACK	20	29	GRAY/BLACK	29
3	BROWN	3	12	ORANGE	12
21	BROWN/WHITE	21	30	ORANGE/BLACK	30
4	LIGHT BLUE	4	13	PINK/WHITE	13
22	LIGHT BLUE/BLACK	22	31	PINK/YELLOW	31
5	LIGHT BLUE/GREEN	5	14	GRAY/GREEN	14
23	LIGHT BLUE/YELLOW	23	32	GRAY/YELLOW	32
6	GREEN	6	15	WHITE/YELLOW	15
24	GREEN/BLACK	24	33	WHITE/GREEN	33
7	BLUE	7	16	LIGHT GREEN/RED	16
25	BLUE/WHITE	25	34	GREEN/BLUE	34
8	WHITE	8	17	LIGHT BLUE/BLUE	17
26	WHITE/BLACK	26	35	LIGHT BLUE/RED	35
9	PINK	9	18	PINK/ RED	18
27	PINK/BLACK	27	36	PINK/BLUE	36
			SHELL	BRAID+DRAIN	SHELL

NOTE:

- CABLE: 28AWG X 18PAIRS(INSULATION: P.P, CONDUCTOR OD= $\varnothing 0.62 \pm 0.05\text{mm}$) AL-FOIL AND BRAID,SHIELDED WITH DRAIN WIRE,UL20276 (IEEE 1284), BEIGE(BG-02) PVC JACKET, MARKING ON PVC JACKET INCLUDE "IEEE 1284-1994 COMPLIANT" ALONG ITS LENGTH. OD= 8.0 ± 0.15
- CONNECTOR: P1 & P2: HALF PITCH 36PIN CENTRONICS MALE: RIBBON AND IDC ASSY TYPE, GOLD PLATED CONTACTS, W/ABS HOOD.
- PACKING: EACH CABLE IN A ZIP-LOCK POLY-BAG.

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE HPCN36M TO HPCN36M				
PART NO. HPCN36PP-MXXXX				