



NOTE:

1. CABLE: 28AWG X 6C, AL-FOIL SHIELDED WITH DRAIN WIRE, NON-UL, BEIGE (BG-03) PVC JACKET. OD:5.0mm.
2. CONNECTOR: P1: MINI DIN 6PIN MALE: SOLDER TYPE, GOLD FLASH CONTACTS; P2: MINI DIN 6PIN FEMALE: SOLDER TYPE, GOLD FLASH CONTACTS.
3. SHIELDING: AL-FOIL TAPE COVER PREMOLD AND 100% CONTACT WITH SHELL.
4. ALL HOOD: MOLDED BEIGE(BG-03) PVC.
5. TESTING:100% ELECTRICAL TESTING.

PIN OUT

P1	_____	P2
1	_____	1
2	_____	2
3	_____	3
4	_____	4
5	_____	5
6	_____	6

SHELL \_\_\_\_\_ SHELL(DRAIN WIRE)

CHART:

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
K8-MD6MF-03	03	914	+50/-0
K8-MD6MF-06	06	1829	+75/-0
K8-MD6MF-10	10	3048	+75/-0
K8-MD6MF-15	15	4572	+75/-0

<b>NET MECHANISM Corp</b> www.cabling-ol.net			
SCALE	NONE		REV A
UNIT	MM		
SHEET	1/1	DWG NO.	
DATE	11/13/04		
TITLE		<b>MD6M TO MD6F</b>	
PART NO.		<b>K8-MD6MF-XX</b>	