



A

B

| L(mm)        | TOLERANCE(mm) |
|--------------|---------------|
| 100~499      | +15/-0        |
| 500~999      | +50/-0        |
| 1000~4999    | +75/-0        |
| 5000~14999   | +150/-0       |
| 15000~49999  | +300/-0       |
| 50000~100000 | +500/-0       |

Specification:

- |                   |                             |
|-------------------|-----------------------------|
| 1. Connector A    | LC/PC S/M Duplex BOOT:WHITE |
| 2. Connector B    | SC/PC S/M BOOT:BLUE         |
| 3. Cable Type     | Duplex S/M $\phi$ 1.8*4.1mm |
| 4. Length         | XX (UNIT:METER)             |
| 5. Jacket Color   | Yellow                      |
| 6. Insertion Loss | <0.20 dB                    |
| 7. Return Loss    | >50.0 dB                    |

|  |          |         |     |   |
|--|----------|---------|-----|---|
| NET MECHANISM Corp<br>www.cabling-ol.net |          |         |     |   |
| SCALE                                    | NONE     |         | REV | A |
| UNIT                                     | MM       |         |     |   |
| SHEET                                    | 1/1      | DWG NO. |     |   |
| DATE                                     | 07/14/05 |         |     |   |
| TITLE                                    |          |         |     |   |
| LC TO SC Singlemode FIBER PATCHCORD      |          |         |     |   |
| PART NO.                                 |          |         |     |   |
| LC-SC-SXX                                |          |         |     |   |