



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL10S-M0050	0.5	500	+50/-0
MIL10S-M0100	1	1000	+50/-0
MIL10S-M0150	1.5	1500	+50/-0
MIL10S-M0200	2	2000	+50/-0
MIL10S-M0300	3	3000	+50/-0
MIL10S-M0500	5	5000	+150/-0

REMARK

- CABLE1:UL2464 28AWG*5P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG-02) OD=6.0±0.15MM
- CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
- 10P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACK OD: 8.0*30MM
TUBE2:HEAT SHRINKING TUBE BLACK OD: 5.0*12MM
- EACH CABLE IN A ZIP PE-BAG

PIN	OUT	OPEN
1	BLACK	
2	BLACK/WHITE	
3	BROWN	
4	BROWN/WHITE	
5	RED	
6	RED/WHITE	
7	ORANGE	
8	ORANGE/WHITE	
9	YELLOW	
10	YELLOW/BLACK	

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04			
TITLE 10P IDC TO OPEN				
PART NO. MIL10S-MXXXX				