



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL10SS-M0050	0.5	500	+50/-0
MIL10SS-M0100	1	1000	+50/-0
MIL10SS-M0150	1.5	1500	+50/-0
MIL10SS-M0200	2	2000	+50/-0
MIL10SS-M0300	3	3000	+50/-0
MIL10SS-M0500	5	5000	+150/-0

REMARK

- CABLE1:UL2464 28AWG\*5P(ID=0.85)+AEB+PVC JACKET;BEIGE(BG-02) OD=6.0? 0.15MM
- CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
- 10P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACK OD: 8.0\*30MM  
TUBE2:HEAT SHRINKING TUBE BLACK OD: 5.0\*12MM
- EACH CABLE IN A ZIP PE-BAG

PIN OUT	
P1	P2
1	BLACK
2	BLACK/WHITE
3	BROWN
4	BROWN/WHITE
5	RED
6	RED/WHITE
7	ORANGE
8	ORANGE/WHITE
9	YELLOW
10	YELLOW/BLACK

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM		DWG NO.	
SHEET	1/1	DATE		
DATE	11/13/04	TITLE		
PART NO.		MIL10SS-MXXXX		