



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL10SS-M0050	0.5	500	+50/-0
MIL10SS-M0100	1	1000	+50/-0
MIL10SS-M0150	1.5	1500	+50/-0
MIL10SS-M0200	2	2000	+50/-0
MIL10SS-M0300	3	3000	+50/-0
MIL10SS-M0500	5	5000	+150/-0

REMARK

1. CABLE1:UL2464 28AWG*5P(ID=0.85)+AEB+PVC JACKET;BEIGE(BG-02) OD=6.0? 0.15MM
2. CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
3. 10P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
4. TERMINAL: Y TYPE TERMINAL
5. TUBE1:HEAT SHRINKING TUBE BLACK OD: 8.0*30MM
TUBE2:HEAT SHRINKING TUBE BLACK OD: 5.0*12MM
6. EACH CABLE IN A ZIP PE-BAG

PIN OUT		
P1		P2
1	BLACK	1
2	BLACK/WHITE	2
3	BROWN	3
4	BROWN/WHITE	4
5	RED	5
6	RED/WHITE	6
7	ORANGE	7
8	ORANGE/WHITE	8
9	YELLOW	9
10	YELLOW/BLACK	10

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM		DWG NO.	
SHEET	1/1	DATE		
DATE	11/13/04	TITLE		
TITLE		10P IDC TO 10P IDC TYPE		
PART NO.		MIL10SS-MXXXX		