



P1	PIN	OUT	OPEN
1	○	BLACK	_____
2	○	BLACK/WHITE	_____
3	○	BROWN	_____
4	○	BROWN/WHITE	_____
5	○	RED	_____
6	○	RED/WHITE	_____
7	○	ORANGE	_____
8	○	ORANGE/WHITE	_____
9	○	YELLOW	_____
10	○	YELLOW/BLACK	_____
11	○	GYEEN	_____
12	○	GREEN/WHITE	_____
13	○	BLUE	_____
14	○	BLUE/WHITE	_____
15	○	PURPLE	_____
16	○	PURPLE/WHITE	_____

CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL16S-M0050	0.5	500	+50/-0
MIL16S-M0100	1	1000	+75/-0
MIL16S-M0150	1.5	1500	+75/-0
MIL16S-M0200	2	2000	+75/-0
MIL16S-M0300	3	3000	+75/-0
MIL16S-M0500	5	5000	+150/-0

REMARK

- CABLE:UL2464 28AWG*8P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG02) OD=7.0±0.15mm
- CABLE2: UL1007,16AWG(26/0.254mm),OD:2.4±0.1mm,COLOR:GN
- 16P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACKØ5.0*12mm
TUBE2:HEAT SHRINKING TUBE BLACK 9.0*30mm
- EACH CABLE IN A ZIP PE-BAG

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	B
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	09/26/13			
TITLE 16P IDC TO OPEN				
PART NO. MIL16S-MXXXX				