



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL16SS-M0050	0.5	500	+50/-0
MIL16SS-M0100	1	1000	+75/-0
MIL16SS-M0150	1.5	1500	+75/-0
MIL16SS-M0200	2	2000	+75/-0
MIL16SS-M0300	3	3000	+75/-0
MIL16SS-M0500	5	5000	+150/-0

REMARK

- CABLE:UL2464 28AWG*8P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG02) OD=7.0±0.15mm
- CABLE2: UL1007,16AWG(26/0.254mm),OD:2.4±0.1mm,COLOR:GN
- 16P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACKφ5.0*12MM
TUBE2:HEAT SHRINKING TUBE BLACKφ9.0*30MM
- EACH CABLE IN A ZIP PE-BAG

P1	PIN OUT	P2
1	BLACK	1
2	BLACK/WHITE	2
3	BROWN	3
4	BROWN/WHITE	4
5	RED	5
6	RED/WHITE	6
7	ORANGE	7
8	ORANGE/WHITE	8
9	YELLOW	9
10	YELLOW/BLACK	10
11	GYEEN	11
12	GREEN/WHITE	12
13	BLUE	13
14	BLUE/WHITE	14
15	PURPLE	15
16	PURPLE/WHITE	16
Y TER	BRAID+DRAIN	Y TER

NET MECHANISM Corp			
www.cabling-ol.net			
SCALE	NONE		REV
UNIT	MM		B
SHEET	1/1	DWG NO.	
DATE	09/26/13	TITLE	
		16P IDC TO 16P IDC TYPE	
PART NO.		MIL16SS-MXXXX	