



P1

CHART:

20P IDC
WITH SR

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL20S-F0010	0.1	100	+15/-0
MIL20S-F0020	0.2	200	+15/-0
MIL20S-F0030	0.3	300	+15/-0
MIL20S-F0050	0.5	500	+50/-0
MIL20S-F0075	0.75	750	+50/-0
MIL20S-F0100	1	1000	+75/-0
MIL20S-F0150	1.5	1500	+75/-0
MIL20S-F0200	2	2000	+75/-0
MIL20S-F0300	3	3000	+75/-0

PIN OUT :

P1 OPEN

- 1 RD _____
- 2 _____
- _____
- _____
- _____
- 20 _____

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE	⊕	REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	07/29/05	TITLE		
		20P IDC TO OPEN		
PART NO.		MIL20S-FXXXX		

Note:

- CABLE : UL 2651 28AWG*(7/0.127mm)*20C , P=1.27MM, GRAY PVC FLAT CABLE .
- P1 CONN : 2.54MM PITCH 10*2=20 PIN IDC SOCKET WITH THREE PARTS.
- THE CABLE SHALL BE 100% ELECTRICAL TEST.