



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL20S-M0050	0.5	500	+50/-0
MIL20S-M0100	1	1000	+50/-0
MIL20S-M0150	1.5	1500	+50/-0
MIL20S-M0200	2	2000	+50/-0
MIL20S-M0300	3	3000	+50/-0
MIL20S-M0500	5	5000	+150/-0

REMARK

- CABLE:UL2464 28AWG*10P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG-02) OD=8.5? 0.15MM
- CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
- 20P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL:Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACK ø 5.0*12MM
TUBE2:HEAT SHRINKING TUBE BLACK ø 10.0*35MM
- EACH CABLE IN A ZIP PE-BAG

	PIN	OUT	OPEN
1	○	BLACK	
2	○	BLACK/WHITE	
3	○	BROWN	
4	○	BROWN/WHITE	
5	○	RED	
6	○	RED/WHITE	
7	○	ORANGE	
8	○	ORANGE/WHITE	
9	○	YELLOW	
10	○	YELLOW/BLACK	
11	○	GYEEN	
12	○	GREEN/WHITE	
13	○	BLUE	
14	○	BLUE/WHITE	
15	○	PURPLE	
16	○	PURPLE/WHITE	
17	○	GRAY	
18	○	GRAY/BLACK	
19	○	WHITE	
20	○	ORANGE/BLACK	

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04	TITLE		
		20P IDC TO OPEN		
PART NO.		MIL20S-MXXXX		