



CHART:

P/N	X(M)	L(MM)	TOLERANCE(MM)
MIL26S-M0050	0.5	500	+50/-0
MIL26S-M0100	1	1000	+50/-0
MIL26S-M0150	1.5	1500	+50/-0
MIL26S-M0200	2	2000	+50/-0
MIL26S-M0300	3	3000	+50/-0
MIL26S-M0500	5	5000	+150/-0

REMARK

- CABLE1:UL2464 28AWG*13P(ID=0.85)+AEB+PVC JACKET:BEIGE(BG-02) OD=8.5? 0.15MM
- CABLE2: UL1007,16AWG(26/0.254MM),OD:2.4±0.1MM,COLOR:GN
- 26P IDC SOCKET,PIN G/F,BLACK THREE PARTS,W/NOSE
- TERMINAL: Y TYPE TERMINAL
- TUBE1:HEAT SHRINKING TUBE BLACK ø5.0*12MM
TUBE2:HEAT SHRINKING TUBE BLACK ø10.0*35MM
- EACH CABLE IN A ZIP PE-BAG

PIN OUT

P1	1	BLACK	OPEN	P1	15	PURPLE	OPEN
	2	BLACK/WHITE			16	PURPLE/WHITE	
	3	BROWN			17	GRAY	
	4	BROWN/WHITE			18	GRAY/BLACK	
	5	RED			19	WHITE	
	6	RED/WHITE			20	ORANGE/BLACK	
	7	ORANGE			21	PINK	
	8	ORANGE/WHITE			22	RED/BLACK	
	9	YELLOW			23	LIGHT GREEN	
	10	YELLOW/BLACK			24	GREEN/BLACK	
	11	GYEEN			25	PINK/BLACK	
	12	GREEN/WHITE			26	PINK/RED	
	13	BLUE					
	14	BLUE/WHITE					

NET MECHANISM Corp www.cabling-ol.net				
SCALE	NONE		REV	A
UNIT	MM			
SHEET	1/1	DWG NO.		
DATE	11/13/04	TITLE		
		26P IDC TO OPEN		
PART NO.		MIL26S-MXXXX		